

# QINGDAO JADE NEW MATERIAL TECHNOLOGY CO.,LTD

青岛杰得佳新材料科技有限公司

# **POLYMER ADDITIVES**

# **JADEWIN LS 119**

# **CHEMICAL COMPONENT**

COMPONENT 1,3,5-Triazine-2,4,6-triamine,N,N-1,2-ethanediylbisN-3-4,6-bisbutyl(1,2,2,6,6-

pentamethyl-4-piperidinyl)amino-1,3,5-triazin-2-ylaminopropyl-N,N-dibutyl-N,N-

bis(1,2,2,6,6-pentamethyl-4-piperidinyl)

CAS 106990-43-6 Molecular C132H250N32

M.W 2286

$$\mathsf{R} - \mathsf{NH} - (\mathsf{CH}_2)_3 - \mathsf{NR} - (\mathsf{CH}_2)_2 - \mathsf{NR} - (\mathsf{CH}_2)_3 - \mathsf{NH} - \mathsf{R}$$

## **SPECIFICATION AND PHYSICAL PROPERTIES**

TEST	UNIT	SPECIFICATION
APPEARANCE		WHITE TO LIGHT YELLOW CRYSTAL SOLID
MELTING POINT	${}^{\sim}$	115-150
VOLATILES	%	1.00MAX
ASH	%	0.10MAX
CLARITY		CLEAR
TRANSMITTANCE		
425nm	%	90.00MIN
450nm		93.00MIN
500nm	%	95.00MIN

# JADEWIN 杰得盈

# QINGDAO JADE NEW MATERIAL TECHNOLOGY CO.,LTD

青岛杰得佳新材料科技有限公司

#### **FEATURE AND APPLICATION**

- \* JADEWIN LS119 is a high molecular weight hindered amine light stabilizer (HALS) which is effective in a broad range of polymers and applications, including polyolefins (PE, PP), TPO, styrenic polymers (ABS, ASA), polyamide fibers, polyurethanes, and elastomers.
- \*The advantages of the product render it particularly useful in PE-based agricultural films, PP fibers, and talc-filled PP and TPO automotive parts. It is also useful in powder coatings where it contributes to the triboelectric effect as well as providing light stability.
- \*JADEWIN LS119 shows a performance synergy with other light stabilizers, including low molecular weight HALS (e.g. JADEWIN LS770, JADEWIN UV3853), high molecular weight HALS (especially JADEWIN LS622), benzoates, and UV absorbers
- \* For additional information please consult the Material safety Data Sheet

#### **Features:**

- -Tertiary HALS having reduced interaction with agricultural chemicals, fillers, pigments, and other additives as compared to conventional HALS
- -Provides outstanding thermal oxidative stability as well as light stability in polyolefins, especially in talc-filled PP and TPO
- -Non-discoloring, low volatility and excellent resistance to migration

## **PACKING**

25KG BAG, 500KG /Pallet, 50KG CARTON

## **STORAGE**

Keep container tightly closed and dry and storage in cool place

# **CHEMICAL INVENTORIES**

Australia - AICS

Canada - DSL

**EU - EINECS** 

China - IECSC

Japan - ENCS

New Zealand - NZIoC

Korea - ECL

USA - TSCA

Philippines - PICCS