


■ POLYMER ADDITIVES

JADEWIN LS 1198

WOOD PHOTOSTABILIZING ADDITIVE

CHEMICAL COMPONENT

COMPONENT	4-Hydroxy-2,2,6,6-tetramethyl-piperidinoxy
CAS	2226-96-2
MOLECULAR	C ₉ H ₁₈ NO ₂
M.W	172



SPECIFICATION AND PHYSICAL PROPERTIES

TEST	UNIT	SPECIFICATION
APPEARANCE		ORANGE TO ORANGE RED CRYSTALLINE POWDER
MELTING POINT	°C	68.0-72.0
VOLATILES	%	0.50MAX
ASH	%	0.10MAX
IMPURITIES	%	0.20MAX
ASSAY	%	99.00MIN

FEATURE AND APPLICATION

*JADEWIN LS 1198 is effective Light Stabilizer intended for WOOD, helping to improve wood coatings and coloration performance and durability.

*JADEWIN LS1198 could stop lignin photooxidation and prevent the premature failure of exterior varnishes and stains and protects wood surfaces from graying and degradation caused by intense UV Light Exposure

*JADEWIN LS 1198 prevents pales shade wood substrates from darkening and yellowing and also



JADEWIN

杰得盈

QINGDAO JADE NEW MATERIAL
TECHNOLOGY CO.,LTD

青岛杰得佳新材料科技有限公司

stabilizes the color of tinted or stained wood, preventing its fading without reducing transparency and brightness.

*JADEWIN LS 1198 is water-soluble and make wood pretreatment easier as dilute aqueous solutions

Application

- Clear wood primers and sealers,
- Industrial and DIY wood stains and tinting solutions
- Wood preservative treatments, sap stain protectants, wood preservers and waterproofers
- penetrating clear and pigmented finishes (i.e. deck coatings)and wood care products, waxes and polishes.
- End use including indoor flooring and furniture and exterior wood and timber: door windows, paneling ,cladding , decking , fencing , shingles beams.

PACKING

25KG Carton , 500KG /Pallet

STORAGE

Keep container tightly closed and dry and storage in cool place

CHEMICAL INVENTORIES

- Australia - AICS
- Canada - DSL
- EU - EINECS
- China - IECSC
- Japan - ENCS
- Korea - ECL
- USA - TSCA
- Philippines - PICCS