



■ POLYMER ADDITIVES

JADEWIN

Waterborne UV-1

SPECIFICATION AND PHYSICAL PROPERTIES

TEST	UNIT	SPECIFICATION
APPEARANCE		LIGHT YELLOW LIQUID
ASSAY	%	≥90
ASH	%	≤0.5
VOLATILES	%	≤1.0

FEATURE AND APPLICATION

- JADEWIN Waterborne UV-1 is suitable for all kinds of aqueous systems UV absorber, will not affect the stability of aqueous systems, in the processing and use of the process to prevent yellowing, improve the weatherability of the material.
- JADEWIN Waterborne UV-1 has good compatibility with most polymers, good dispersion, and can be directly added to water.
- JADEWIN Waterborne UV-1 is recommended to be added at 0.5%-2%.
- For additional information please consult the Material Safety Data Sheet.

PACKING

25KG PE Drum,180KG Metal Bucket

STORAGE

Keep container tightly closed and dry and storage in cool place

CHEMICAL INVENTORIES

Australia - AICS
Canada - DSL
EU - EINECS
China - IECSC
Japan - ENCS
Korea - ECL
USA - TSCA



JADEWIN

杰得盈

Philippines - PICCS

QINGDAO JADE NEW MATERIAL
TECHNOLOGY CO.,LTD
青岛杰得佳新材料科技有限公司