



## ■ POLYMER ADDITIVES

### JADEWIN

## Waterborne LS 292

#### SPECIFICATION AND PHYSICAL PROPERTIES

TEST	UNIT	SPECIFICATION
APPEARANCE		COLORLESS TO LIGHT YELLOW OILY TRANSPARENT LIQUID
ASSAY	%	90MIN
ASH	%	0.1MAX
VOLATILES	%	0.5MAX
TGA(10%)	°C	270

#### FEATURE AND APPLICATION

- JADEWIN Waterborne LS 292 is a special light stabilizer for waterborne coatings, which can effectively prevent waterborne coatings from bursting and surface peeling under sunlight exposure.
- JADEWIN Waterborne LS 292 is compatible with waterborne coatings without affecting their stability, and has good dispersibility, so it can be added into water directly.
- JADEWIN Waterborne LS 292 is mainly used in waterborne color paint coating system to prolong the service life of the finished product, but it is not applicable to acidic system. It is recommended to add 0.5%-2%.
- For additional information please consult the Material Safety Data Sheet.

#### PACKING

25KG PE Drum

#### STORAGE

Keep container tightly closed and dry and storage in cool place

#### CHEMICAL INVENTORIES

Australia - AICS  
Canada - DSL  
EU - EINECS



JADEWIN

杰得盈

QINGDAO JADE NEW MATERIAL  
TECHNOLOGY CO.,LTD  
青岛杰得佳新材料科技有限公司

China - IECSC

Japan - ENCS

Korea - ECL

USA - TSCA

Philippines - PICCS