

■ POLYMER ADDITIVES

JADEWIN UV309

SPECIFICATION AND PHYSICAL PROPERTIES

TEST	UNIT	SPECIFICATION
APPEARANCE		LIGHT YELLOWISH POWDER

FEATURE AND APPLICATION

- JADEWIN UV 309 absorbs ultraviolet rays in the range of 290-400nm. It is applicable to polymer materials such as PE, PP, PVC, PET/PBT, POM, PS, ABS, ASA resins, epoxy resins, resin fibers, vinyl acetate, oil-based coatings, inks and adhesives, delivering excellent light stabilization performance.
- JADEWIN UV 309 can be used alone or compounded with other antioxidants and light stabilizers, including phosphites, hindered phenols, sulfur-containing antioxidants, hindered amine light stabilizers (HALS), etc.
- JADEWIN UV 309 contains no EU SVHC (Substances of Very High Concern), and can replace UV absorber 329 which is listed in the EU SVHC candidate list.
- The recommended dosage is more than 0.6%. The specific addition amount shall be determined according to product processing, service requirements and practical tests.

PACKING

25Kg

STORAGE

Keep container tightly closed and dry and storage in cool place

DISCLAIMER

* The information provided is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.